



**PLUMBING:**

- 20mm NB(3/4") HOT & COLD WATER SUPPLY LINES  
MAX PRESSURE 7 BAR (100 PSI)  
4 BAR (60 PSI) TO 5 BAR (70 PSI) RECOMMENDED.  
FIT SHUT OFF VALVES AND SERVICEABLE STRAINERS  
IN WATER SUPPLY LINES.
- 50mm (2") FLOOR DRAIN FOR ROOM.
- 50mm (2") DRAIN FOR TABLE DRAIN CONNECTION.
- APPROXIMATELY 150 LITRES (40 GALLONS) USED FOR A (20) TWENTY  
MINUTE TREATMENT. BASED UPON HYDROCO TREATMENT  
ASSUME 75 LITRES (20 GALLONS) OF THIS BEING HOT WATER  
BASED ON THE EXPECTED NUMBER OF TREATMENTS DAILY AN  
APPROPRIATE HOT WATER SUPPLY NEEDS TO BE INSTALLED.

**NOTE:** INSTALL IN ACCORDANCE WITH LOCAL AND NATIONAL  
CODE REQUIREMENTS.

**LEGEND:**

- 50mm (2") FLOOR DRAIN - FOR TABLE DRAIN CONNECTION
- 50mm (2") FLOOR DRAIN - FOR ROOM DRAIN
- HW ● 20mm (3/4") HOT WATER CONNECTION
- CW ● 20mm (3/4") COLD WATER CONNECTION
- ⊕ 40mm (1 1/2") TABLE DRAIN (IN TABLE)

HYDROWOOD 7 WEIGHT - 70kg

**HYDROCO (AUST) PTY LTD**  
SEAFORD VICTORIA AUSTRALIA  
ph. +61 3 8770 4000 www.hydroco.com fax. +61 3 9773 6122

# HYDROWOOD WITH HAND SHOWER - LAYOUT SPECIFICATION

DRG No. HW-INST-005

16 JULY 2008

NOTE! THIS DRAWING IS TO BE USED AS A GUIDE ONLY AND IS SUBJECT TO CHANGE WITHOUT NOTICE