



NOTE:- THIS IS TO BE USED AS A GUIDE ONLY, THE MANUFACTURER RESERVES THE RIGHT TO AMEND SPECIFICATIONS WITHOUT PRIOR NOTICE

\* IN-WALL PLUMBING REQUIRED AS PER ABOVE .

\* 1/2" BRASS ALL THREAD TO PROTRUDE THROUGH ROOF APPROX 2" ( 50 mm ) IN LENGTH - DRENCH SHOWER

\* 1/2" BRASS ALL THREAD TO PROTRUDE THROUGH ROOF APPROX 1" ( 25 mm ) IN LENGTH - STEAM RING

\* SUPPLY WATER PIPES - 1" ( 3/4" MINIMUM )

\* WATER PRESSURE REQUIRED - 50 PSI + ( 3.4 Bar + ) OPTIMUM 70 PSI ( 4.8 Bar )

SHEET 1 OF 1

**HYDRO**co  
KNOW THE DIFFERENCE™

**HYDROSWISS**

**In-Wall Configuration  
with Steam Ring**

www.hydroco.com

HydroCo ( Australia ) Pty. Ltd. HydroCo ( USA )

+61 3 8770 4000 - PHONE

31 0.381.0071 - PHONE

+61 3 9773 6122 - FAX

31 0.381.0072 - FAX